



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

Date: 01-DEC-2025

Quote Number: QU37099-TU- V1

Unit: TL100

**JACK DOHENY COMPANY**  
777 DOHENY DR  
NORTHVILLE , MI 48167-1957

**Qty. Description**

UNIT

1 **TI100 Telescopic Transmission Aerial**

One (1) new Terex Hi-Ranger TL100 Articulating / Telescoping Aerial Device providing a working height of 100.0 ft (30.5 m).  
Unit will be mounted over the rear axle.

Design Criteria:

\* Design criteria is in accordance with current industry and engineering standards applicable and accepted for structural and hydraulic design.

Aerial device is designed as a Category C machine in accordance and is dielectrically tested and rated for operation on systems up to 46 Kv phase to phase per ANSI/SIA A92.2-2021

Turntable and Lower Boom Assembly:

Lower Boom:

\* Filament wound high strength fiberglass insert providing an insulation gap.  
\* The lower boom articulation is from 0 to 88 degrees.

Lower Controls:

\* Individual control levers are located in an accessible location on the turntable.

Rotation:

\* Self-locking worm gear rotation drive is provided and equipped with bi-directional motor.

Hydraulic System:

\* Full pressure open center hydraulic system.  
\* Hydraulic hoses are equipped with permanent type fittings.

Miscellaneous:

\* All metallic components of the complete aerial device are powder painted white.  
\* The fiberglass upper boom, boom inserts, platforms and covers are white.  
\* One complete paper manual and access to an electronic copy of the manual providing operational and maintenance procedures, and a replacement parts listing.  
\* Warning decals provided with unit.

Continuous And Unrestricted Rotation:

\* A hydraulic rotary manifold provides a rotating oil distribution system for continuous and unrestricted rotation.  
\* A 6 channel electric collector ring is provided as standard.

Boom Stow Protection System:

\* Protects against damage from excessive down pressure of the lower boom by cutting off oil supply to the lower boom function.

Upper Boom Rest:

A boom rest with a cam style tie down strap is provided.

1 **Pedestal,45.37**



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

**Date: 01-DEC-2025**

**Quote Number: QU37099-TU- V1**

**Unit: TL100**

**Pedestal:**

\* The pedestal is designed with access holes for maintenance of hydraulic plumbing.

**1 Boom Tip,End,Rot,Transmission Style Jib**

Boom Tip with 4 Function Controls, Platform Rotator and 1000 lb. top mounted jib.

Upper Controls: Control-Plus single stick controller.

\* Enable lever must be actuated before operation.

The end mount platform rotator offering 180 degrees of hydraulic rotation.

Hydraulic Platform Tilt is provided at platform and lower controls.

Engine Stop/Start controlled at platform and lower controls.

Upper Boom:

\* Filament wound high strength fiberglass boom providing an insulation gap.

Dual Hydraulic Tool Outlets At Platform With Flow Control:

\* Installed at the platform to accommodate two open center hydraulic tools.

\* Provides 5 GPM at 2250 psi at engine idle.

Hydraulic Articulating Hydraulic Extending 90 Degree Jib And Winch:

\* Infinite positioning through the 90 degree articulation envelope

\* Jib length is 48 retracted a hydraulic extension of 17 and a manual extension of 15.75 (2 positions at 7.88 )

\* Jib extends by means of a hydraulic cylinder.

\* Can extend under load.

\* Jib capacity is 1000-lbs with jib retracted.

\* 120' of 3/8 load line and swivel hook with latch.

\* Includes a winch control at the lower controls.

**1 Jib Chart With 600 Lbs Platform Capacity**

600 lbs. Rated Platform Capacity.

**1 End Mount, 24x48**

Platform, End Mount, 24 x 48 x 42:

\* Includes one outside access step with slip-resistant surface.

**1 Customer Declined - Fall Arrest Harness**

Customer Decline Fall Arrest.

**1 Platform Rest,Single,24x48,Lifter**

A rigid platform rest provides platform support during road travel.

**1 Demand Throttle**



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

**Date: 01-DEC-2025**

**Quote Number: QU37099-TU- V1**

**Unit: TL100**

**Throttle System:**

When the PTO switch is activated the engine RPM's will increase slightly above idle to a preset level. The engine RPM's are preset for appropriate hydraulic oil flow GPM for unit operation according to PTO/pump combination.

**1 Auxiliary Letdown,12v**

**Auxiliary Let Down for use with Open Center Hydraulics:**

\* Allows for the descent of the boom (platform) in the most direct manner for a time limited by the duty cycle of the electric motor.

\*Includes 12 volt electric motor for use on a 12 volt chassis.

Note: This includes a switch for activation at pedestal for electric or air function.

**1 0 To 69 Kv Rating For Cat B**

Aerial device is designed as a Category B machine in accordance with ANSI/SIA A92.2-2021.

\* Include: lower test electrode system and system to prevent vacuum in individual hydraulic lines.

\* Terex South Dakota Inc. can only test up to 69KV when this option is ordered.

\* Can be rated from 46KV up to 69KV per ANSI/SIA A92.2-2021 depending on: model, options and fiberglass length.

\* Must specify KV rating when ordering.

**1 Terex Advanced Chassis Controller**

**Terex Advanced Chassis Controller:**

\* Multiplexed system to include: Controller, LCD Screen, Manual and Schematics.

\* Standard Options: Diagnostics, Status Screens, Event Log, Hours Meter, Selectable Button Labels, System Alerts and System Test.

\* Programmable settings allow installer to customize/select options need for their application.

\* Screw terminal-type connections and enclosure to cover connections.

\* Recommended on Class 6 and above chassis with multiple outputs

\* The PTO hour is standard. The engine hour meter is standard (When available). This is a message we get from the truck Data link. All trucks except Ford give us the Engine hours. So if it's a Ford, we just display PTO hours.

**1 Subframe For 163 Inch Ct - 204 Inches Long - Class 1**

Subframe constructed with an open center.

**1 Tie Down Kit TI100**

Tie down kit.

**1 Radial (468029)**

Radial Outriggers with swivel type stabilizer pads. (468029)



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

Date: 01-DEC-2025      Quote Number: QU37099-TU- V1      Unit: TL100

1      **Radial (468029)**

Radial Outriggers with swivel type stabilizer pads. (468029)

1      **O/R Controls, 2 Sets W/Tool Outlet**

Controls For 2-Sets Of Outriggers And Auxiliary Tool Outlets (Open center systems):

- \* Recessed at rear of truck each side for ease of view for outrigger placement.
- \* Includes switches and alarm for outrigger in motion alarm.

1      **Adjustable Flow Divider**

Adjustable flow divider for auxiliary tool outlets below rotation.

1      **Outrigger Interlock,12v,Std (2 Sets Radials)**

Outrigger Interlock:

- \* To operate the boom the outriggers must be extended.

1      **Pump, Vane, 14 Gpm, Cw, (Auto)**

Pump for systems requiring 14 gallons per minute:

- \*Fixed displacement vane pump providing 6 gallons per minute at 700 engine rpm and 12 gallons per minute at 1400 engine rpm with a 95% pto.

1      **50 Gal Bed Mnt Reser W-Sight & Temp Gage**

Hydraulic Reservoir:

50 gallon hydraulic oil reservoir includes 10 micron replaceable cartridge type return line filter mounted in reservoir with bypass valve incorporated in filter to prevent restricted flow.

- \* A 100 mesh in screen in filter cap. A 40 mesh screen included in tank outlet and a ball type shut off valve.

\* Relief valves to protect the circuit.

Sight Gauge With Thermometer:

- \* Mounted within an aluminum body to protect sight tube.
- \* Installed on end of hydraulic oil reservoir.
- \* Thermometer has a range of 0-300 degrees Fahrenheit.

1      **Usa**

American flag displayed on unit.

1      **Limited Product Warranty - Standard**

Factory Warranty

1      **Customer Disclaimier On Customer Supplied Chassis**



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

Date: 01-DEC-2025

Quote Number: QU37099-TU- V1

Unit: TL100

Customer Supplied Chassis:

- \* Along with the purchase order the customer will be required to include a copy of the chassis specification intended for use and the contact information of the supplying chassis dealer. If the chassis specification does not meet minimum requirements for the application additional costs may be incurred to meet those requirements.
- \* Terex Utilities, Inc. requires a weight study analysis to insure chassis loading and stability.
- \* Chassis's delivered to the installation facilities that do not meet minimum specification requirements will be noted at time of delivery and a suggested resolution will be provided back to the customer.
- \* Reference Terex Customer Furnished Chassis Delivery Policy for additional instructions.

1 **245.5" Flatbed w/40" transverse Body and accessories per attached specifications.**

1 **Install TI Behind Cab**

Install Aerial Device Behind Cab And Install All Associated Components:

- \* Final test and inspect completed unit including stability and dielectric testing per manufacturers requirements.

1 **Hose & Fitting Kit Group 1**

Hose and fittings to connect the hydraulic system from the oil reservoir to the pump and unit.

1 **Misc Shop Supplies Group 3**

Miscellaneous shop supplies.

1 **Platform Rest Bottom Base Group 3**

Platform rest, bottom base

1 **Chassis Spring Add Left Rear( Req. Art)**

Chassis Spring Additions:

- \* Build up left rear chassis springs to level vehicle.

1 **Pto (Muncie) For Automatic Transmission**

Power take off with indicator light for automatic transmission.

1 **Dot Inspection**

DOT Inspection.

1 **Set Chassis Parameters ( Req'D)**



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

Date: 01-DEC-2025      Quote Number: QU37099-TU- V1      Unit: TL100

Set chassis parameters.

1    **Ecco Back-Up Alarm**

Back-up alarm to sound when the vehicle is shifted into reverse.

4    **Wood 24 X 24 Painted Black (Standard)**

Laminated wood outrigger pad 24 x 24 x 2-1/4 with rope handle.

4    **Rubber Wheel Chock Eye Bolt (Standard)**

Rubber wheel chocks with eye bolt.

1    **Grab Handle Set Three Point Contact**

Grab Handle set for three point contact.

1    **Cable Stirrup Step ( Standard )**

Cable type gripstrut stirrup step.

1    **Access Step ( Standard )**

Access steps to platform from top of body or flatbed floor.

2    **Mud Flap - Terex Logo (Standard)**

Mud flap with logo.

Note: Trim As-Required.

1    **Mounting Bracket For Grounding Cable**

Bracket for storing grounding cable.

1    **Kit Ground Cable 2/O Black (Standard)**

2/0 Black Electrical Cable used for grounding per ASTM F855-04:

\* 50' of multi-strand flexible copper cable, three grounding lugs, two ferrules and grounding clamp.

\* Three point grounding system for grounding vehicle during work operations.

\* Cable must be fully removed from bracket before use.

NOTE! Purchaser to verify this meets their company's requirements for fault current.

1    **Boom Rest Aerial Radial Outriggers**



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

Date: 01-DEC-2025

Quote Number: QU37099-TU- V1

Unit: TL100

Boom rest for Aerial.

1 **Peterson 7-Lamp Led Kit Fmvss Dot**

Peterson LED 7-lamp DOT Lighting Package:

- \* Complies with FMVSS 108.
- \* Includes required lights, junction box and wiring harness.
- \* Note: Includes lighted License Plate Area
- \* Note: Includes Clearance Lights if Applicable to application.

2 **Kit 4 Amber Led Strobe Light/Guard(Std)**

Amber strobe light (LED) with 4 inch tall and 6 inch diameter lens and branch guard.

2 **Recovery Tow Eye 5 X16 X1 29 000lb Rate**

Recovery tow eye, 29,000#.

1 **Stop/Start Rear Of Truck**

Remote engine stop/start control from rear of vehicle.

1 **Two Speed Rear Of Truck**

Remote two speed control from rear of vehicle.

1 **Icc Rear Bumper**

ICC rear bumper.

1 **Oil Tank Mounting (Req For External)**

Oil tank mounting for external reservoirs.

60 **Hydraulic Oil - General Purpose**

Fill with Hydraulic oil for general purpose use.

\* Refer to the product maintenance manual for specific type to be used.

1 **Safety Kit 5# Fire Extinguisher-Abc(Std)**

Safety Kit consists of the following:

- \* 5-lb ABC fire extinguisher with bracket.
- \* James King triangle reflector kit.



Terex USA, LLC dba Terex Utilities - 3140 15th Avenue SE - Watertown, SD 57201 - Phone: 605-882-4000

**Date: 01-DEC-2025      Quote Number: QU37099-TU- V1      Unit: TL100**

**1      Fire Extinguisher 5# Abc**

5-lb ABC fire extinguisher with bracket.

**1      Paint Flatbed Over 17'**

Paint flatbed one color over 17'.

\*Note - Paint under carriage black.

**1      Paint Body Floor With Non-Skid Paint**

Paint body floor with non-skid paint.

**1      Paint Compartment Top Non-Skid Paint**

Paint compartment top with non-skid paint.

**2      Paint Radial O/R'S (1 Set) Ilo A Frame**

Paint radial outriggers (1 set) ILO A frame one color.

**Terex USA, LLC dba Terex Utilities**

1. Federal Excise Tax will be added if certificate is not supplied with order.
2. The following items must be considered by the purchaser if not already included: Strobe Light; Wheel Chocks; Outrigger Pads; Outrigger Out of Stow Light; Truck Grounding Kit; Barricade Kit; Boom Stow Interlock; Auxiliary Let Down; Platform Liner; Platform Cover; Two-Speed; Start/Stop Controls; Oil Cooler; PAL; Anti-Two Block (Digger Derricks); Load Display (Digger Derricks) and Load Alert (Aerials).
3. Terex USA, LLC dba Terex Utilities strongly recommends all installation accessories be located up front in front in the quote or secondarily on the approved engineering drawing. Any accessories located or relocated during manufacturing may be subject to additional charges.
4. Terex USA, LLC dba Terex Utilities - Offers In-service Training.
5. Terex USA, LLC dba Terex Utilities - Assembly in Watertown, South Dakota is ISO 9001:2000 Certified.

<b>Quotation Number</b>	<b>17064</b>
For the attention of	<b>Doug Pahl</b>
<b>Customer:</b>	<b>Terex Jack Doheny Co.</b>
	Date <b>11/12/2025</b>

### **DESCRIPTION**

#### **T-40-02 Transverse Body 48 inches high X 94 inches wide.**

16 Ga. body materials.  
 12 Ga. treadplate compartment tops.  
 24 Inch compartment depth.  
 Slam action paddle type door latches.  
 Stainless steel rod and socket type door hinges.  
 Chain stops on all doors.  
 Double Panel Body Doors.  
 Automotive Bulb Type Weatherstripping.  
 Top rail package installed on top of transverse compartment.  
 \* 12" High at front and 8" High on sides

#### **245.5" Treadplate Flatbed 94 inches wide.**

12 Ga. Treadplate floor.  
 6" structural steel JR I-Beam crossmembers on 12" centers.  
 4" High steel flat perimeter retainer, corners notched, welded to flatbed.  
 \* Two (2) Removable 23" L sections at rear.  
 Valve mounting plates on SS & CS of flatbed.  
 9-Lamp light bar installed at rear.

#### **Streetside Compartmentation:**

##### **1st Vertical:**

40 Inches wide with Four (4) fixed material hooks 2-0-2.

Barn type compartment doors.

#### **Curbside Compartmentation:**

##### **1st Vertical:**

40 Inch wide transverse compartment with a 66" tool board and track in Front portion.

Front of board has Five (5) material hooks, rear has a full length tray, oak bit holder and peg hook.

Three (3) material drawers each with adjustable dividers on 6 inch centers in rear portion.

\* Top drawer is 4" high and lower 2 drawers are 6" high  
Transverse drawers each include a latch and are mounted on Roller Bearing Slides.  
One fixed through shelf on top of drawer set.  
Barn type compartment doors.

**CS Access Steps:**

24 Inch wide Gripstrut access steps to bed area.  
Removable 4" high steel retainer X full width of step area.

**Subframe Installation:**

Install customer supplied subframe, with outriggers.  
\* Two (2) Radial Outriggers.

**Powder Coat Body:**

Powder Coat Body and Inside of compartments Taffeta White.



**Peterbilt Of Wisconsin (P123)**  
820 Silvenail Rd. Suite A  
Pewaukee, Wisconsin 53072

**Jack Doheny Companies**  
777 Doheny Dr  
Northville, Michigan 48167  
United States of America

**Todd Roskopf**  
Cell Phone:  
Office Phone: (262)547-0001  
Email: [troskopf@jxe.com](mailto:troskopf@jxe.com)

**Ryan Rozycki**  
Office Phone: 248-349-0904

## Vehicle Summary

<b>Unit</b>		<b>Chassis</b>	
Model:	Model 548	Fr Axle Load (lbs):	18000
Type:	Full Truck	Rr Axle Load (lbs):	40000
Description 1:	JDC Tandem Pete Terex	G.C.W. (lbs):	58000
Description 2:	TL100 Terex Peterbilt 548 Tandem JDC Terex FTL to PETE		
<b>Application</b>		<b>Road Conditions:</b>	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
<b>Body</b>		<b>Maximum Grade:</b>	
Type:	Van		6
Length (ft):	24	Wheelbase (in):	230
Height (ft):	13.5	Overhang (in):	157.2
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	69.5
<b>Trailer</b>		<b>Cab to Axle (in):</b>	
No. of Trailer Axles:	0	<b>Cab to EOF (in):</b>	
Type:		<b>Overall Comb. Length (in):</b>	
Length (ft):	0		427.2
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
<b>Restrictions</b>			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		
<b>Approved by:</b>		<b>Date:</b>	

**Note: All sales are F.O.B. designated plant of manufacture.**



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
<b>Base Model</b>				
0005481	S	<b>Model 548</b> The Model 548 meets and exceeds the demands of Class 8 specialty application markets that require a rugged workhorse for durability and a wide range of optional content. The Model 548 is available in configurations with a GVW from 33,001 to 66,000 lbs. to suit most vocational applications. The 548 also offers all-wheel-drive. From construction and crane service to utility and delivery services in Class 8 markets, the 548 is in a class of its own.	124,529	<b>10,860</b>
0091200	S	<b>Other Commodity</b>	0	<b>0</b>
0093340	S	<b>City Delivery</b> Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	<b>0</b>
0095040	S	<b>Van</b>	0	<b>0</b>
0098170	S	<b>United States Registry</b> Canadian Registry PackageRequires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	<b>0</b>
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	<b>0</b>
<b>Frame &amp; Equipment</b>				
0515040	O	<b>10-5/8" Steel Rails 385-444"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	491	<b>512</b>
0601500	O	<b>Full Steel Inner Liner</b>	2,071	<b>805</b>
0611300	S	<b>Heavy Duty 5-Piece Crossmember BOC IPO Standard</b> Class 5, 6, 7	0	<b>0</b>
0611790	S	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	0	<b>0</b>
0612230	O	<b>Custom Wheelbase or Overhang</b> Engineering approval may be required.	350	<b>0</b>
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0	<b>0</b>
0651090	O	<b>Omit Rear Mudflaps and Hangers</b>	-61	<b>-25</b>
<b>Front Axle &amp; Equipment</b>				
1011890	O	<b>PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop</b> Axe is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding	2,364	<b>137</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.		
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.		
1113020	O	<b>Taper Leaf Springs, Shocks 18,000 lb</b> Standard with Heavy Resistance Shocks.	276	<b>118</b>
1243050	O	<b>Power Steering Sheppard HD94 Dual Gear</b> For use with 16,000 to 20,000 lb. axle ratings.	1,100	<b>80</b>
1250250	O	<b>Power Steering Reservoir Frame Mounted w/Cooler</b> A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	161	<b>2</b>
1354840	S	<b>PHP10 Iron PreSet PLUS Hubs</b> PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	0	<b>0</b>
1380490	O	<b>PACCAR FX Wide Track IPO Standard</b> 71in KPI IPO 69in front axle for improved turning radius.	0	<b>15</b>
1381460	O	<b>Meritor Q+ Air Cam Front Drum Brakes 16.5 x 7</b> Not Reduced Stopping Distance (RSD) compliant. Meritor Q+ Air cam front drum brakes for truck/trailer linehaul and vocational applications. The Q+ offers longer lining life and helps fleets meet reduced stopping distance regulations. For use with 10,000-13,200 lbs. steer axles, up to and including 40,000 lbs. drive axles and up to 20,000 lbs. lift axles. Requires Meritor Q+ Air Cam Rear Drum Brakes.	299	<b>10</b>
1391410	S	<b>Gusseted Cam Brackets, Steer Axle</b>	0	<b>0</b>

## Rear Axle & Equipment

1526150	O	<b>Meritor MT40-14X 40,000 lb</b> Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	10,598	<b>1,974</b>
1616300	S	<b>PHP10 Iron PreSet PLUS Hubs</b>	0	<b>0</b>
1660000	O	<b>Dust Shields For Cam Brakes, Drive Axle(s)</b>	54	<b>15</b>
1680450	O	<b>Rear Brake Camshaft Reinforcement</b> Rear brake camshaft reinforcement helps guard against wear and corrosion.	16	<b>9</b>
1680460	O	<b>Heavy Wall, Drive Axle(s)</b>	1,019	<b>88</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	<b>0</b>
1680525	O	<b>Pneumatic Park Brake</b>	0	<b>0</b>
1680750	O	<b>Meritor Q+ Air Cam Rear Drum Brakes 16.5x7</b>	110	<b>0</b>
1680950	S	<b>Stability System Not Selected Or Not Available</b>	0	<b>0</b>
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0	<b>0</b>
1683245	S	<b>Tire Pressure Monitoring System</b>	381	<b>25</b>
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	<b>0</b>
1687090	O	<b>Diff Lock Tandem Axles</b> With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	1,930	<b>60</b>
1705860	O	<b>Ratio 5.86 Rear Axle</b>	0	<b>0</b>
1824400	O	<b>Hendrickson HMX EX 400 40,000 Lbs., 54"</b> Haulmaax, 60K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	5,754	<b>523</b>
1921475	O	<b>Shock Absorbers For HMX EX Suspension</b>	457	<b>31</b>
1921965	O	<b>HMX EX Double Rebound Strap Kit</b>	246	<b>6</b>
<b>Engine &amp; Equipment</b>				
2074805	O	<b>PACCAR PX-9 330@2000 GOV@2200 1000@1200</b> Productivity (2024 Emissions)  N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera	2,391	<b>0</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
		N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown ( N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume ( N21430 C333 0.....Reserve Speed Limit Offset ( N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 100...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)		
2091120	S	<b>EMUX Electronics Architecture</b>	0	<b>0</b>
2091305	O	<b>Engine Idle Shutdown Timer Enabled</b>	0	<b>0</b>
2091315	O	<b>Enable EIST Ambient Temp Overrule</b>	0	<b>0</b>
2091372		<b>Eff EIST NA Expiration Miles</b>	0	<b>0</b>
2091640		<b>Effective VSL Setting NA</b>	0	<b>0</b>
2092014	O	<b>Typical Operating Speed 65 MPH</b>	0	<b>0</b>
2092032	O	<b>Powertrain Optimized for Performance</b> Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	<b>0</b>
2140200	O	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	<b>0</b>
2140460	S	<b>Remote PTO/Throttle, 12-Pin, 250K BOC/BOS</b> J1939, Remote Control Provision	0	<b>0</b>
2140660	O	<b>CARB Emission Warranty</b>	0	<b>0</b>
2140700	S	<b>EPA Engine Idling Compliance</b>	0	<b>0</b>
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	<b>0</b>
2521090	O	<b>Immersion Type Block Heater 110-120V</b>	102	<b>2</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
		Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.		
2522110	S	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b> PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	<b>0</b>
2538120	O	<b>3 PACCAR AGM 12V Batteries 2775 CCA</b>	533	<b>62</b>
2539410	O	<b>Battery Jumper Terminal Mounted Under Hood</b> LH Frame Rail. Not available with PX-7 engines.	153	<b>4</b>
2539550	O	<b>Batteries In In-Cab Battery Box</b>	0	<b>0</b>
2539720	O	<b>Low Voltage Disconnect System</b>	0	<b>0</b>
2621090	S	<b>HORTON ON/OFF Fan Clutch</b>	0	<b>0</b>
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	<b>0</b>
2812210	S	<b>VGT Exhaust Brake</b> (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0	<b>0</b>
2921110	S	<b>PACCAR Fuel/Water Separator Standard Service</b> PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	<b>0</b>
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0	<b>0</b>
2921310	S	<b>No Electric Heat Option for Fuel Filter</b>	0	<b>0</b>
3010400	O	<b>Engine Protection Shutdown w/ Label</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	<b>0</b>
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.	0	<b>0</b>
3211140	S	<b>(1) Air Cleaner Engine Mounted</b>	0	<b>0</b>
3367160	O	<b>Exhaust Single RH Side of Cab</b> DPF/SCR RH Under Cab, Single Module	1,088	<b>40</b>
3381770	O	<b>Curved Tip Standpipe(s)</b>	42	<b>1</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
3387370	O	<b>60" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	387	<b>14</b>
<b>Transmission &amp; Equipment</b>				
4052930	O	<b>Allison 3500 RDS-P Transmission, Gen 6</b> Rugged Duty Series	7,930	<b>459</b>
4210080	S	<b>1710 HD Driveline, 1 Midship Bearing</b>	0	<b>0</b>
4216590	O	<b>1710 Driveline Interaxle</b> For tandem rear axles	0	<b>0</b>
4230080	O	<b>PTO F/O Chelsea</b>	0	<b>0</b>
4233900	O	<b>(1) Dash Mounted Single Acting EOA PTO Control</b> Electric-over-air (EOA), spec'ing PTO (power-take-off) control switch does not ensure the PTO will fit.	83	<b>1</b>
4252890	O	<b>Allison FuelSense Not Desired</b> Dynamic Shift Sensing	0	<b>0</b>
4252940	O	<b>Allison Neutral At Stop</b> Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO <sub>2</sub> emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	<b>0</b>
4256680	O	<b>Allison 6-Speed Configuration, Wide Ratio Gears</b>	0	<b>0</b>
4256870	O	<b>Allison Output Function S Neutral Indicator</b> Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	<b>0</b>
4256920	O	<b>Dash Mounted Push Button Shifter</b> Available with Allison transmissions	565	<b>3</b>
4257110	O	<b>LH Mounted Trans PTO Provisions</b>	36	<b>0</b>
<b>Air &amp; Trailer Equipment</b>				
4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	<b>0</b>
4520420	O	<b>Pull Cords All Air Tanks</b>	4	<b>0</b>
4540420	S	<b>Nylon Chassis Hose</b>	0	<b>0</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	<b>0</b>
4611730	O	<b>7-Way Electric Harness, Socket Mounted EOF</b>	236	<b>10</b>
<b>Tires &amp; Wheels</b>				
5064020	O	<b>FF: BR 18ply 385/65R22.5 M864</b> Efficiency Rating: Poor Diameter= 42.9 inches; SLR= 19.8 inches	861	<b>122</b>
5104230	O	<b>RR: CN 14ply 11R22.5 HDR2+</b>	532	<b>176</b>
5190008	O	<b>Code-rear Tire Qty 08</b>	0	<b>0</b>
5215280	O	<b>FF: Accuride 29683SP 22.5x12.25 Aluminum Wheel</b> Standard polish, 2.88in inset	854	<b>4</b>
5310600	O	<b>RR: Accur Stl Armor 50291PK 22.5X8.25</b> Heavy Duty, Two Hand Holes	392	<b>160</b>
5390008	O	<b>Code-rear Rim Qty 08</b>	0	<b>0</b>
<b>Fuel Tanks</b>				
5584070	O	<b>D-Shaped Aluminum 60 Gallon Fuel Tank LH U/C</b> Non-slip step LH under cab	48	<b>-5</b>
5602060	O	<b>Location LH U/C 60 Gallon</b>	0	<b>0</b>
5652830	O	<b>Polish All Fuel / Hydraulic Tank Straps</b> Does not apply to rectangular DEF tank straps	12	<b>0</b>
5652900	O	<b>DEF Tank Mounted LH Under Cab</b>	55	<b>0</b>
5652980	S	<b>DEF To Fuel Ratio Between 1:1 And 2:1</b>	0	<b>0</b>
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	<b>0</b>
5660570	O	<b>(1) Low Flex Step U/C, Aftertreatment Only</b>	307	<b>11</b>
<b>Battery Box &amp; Bumper</b>				
6010390	O	<b>Omit Standard Battery Box</b> Use with passenger seat/in-cab battery box codes only	-310	<b>-44</b>
6040550	S	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b>	0	<b>0</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
		Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.		
6112840	O	<b>Steel Bumper Tapered Chromed</b> Two tow points. ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height:  Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	761	115
<b>Cab &amp; Equipment</b>				
6510190	O	<b>Peterbilt Aero 109in BBC SMC Hood</b> With molded charcoal crown and aluminum cab.	1,829	15
6540160	O	<b>Thermal Insulation Package in Cab</b> The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	73	2
6800180	O	<b>Hood Crown - Bright Finish ipo Molded Gray</b>	110	0
6914180	S	<b>Sears Driver Seat</b>	0	0
6924200	O	<b>Sears (2) Person Passenger Seat</b>	984	-10
6930500	O	<b>Drivers Armrest - RH Only</b>	28	2
6930800	O	<b>Black Seat Color IPO Standard Color</b>	0	0
6939100	O	<b>Battery Box Under Passenger Seat</b> Only available with non-adjustable seat or no furnished passenger seat. Includes disconnect switch.	3,476	40
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	O	<b>High Back Driver</b>	44	0
6939470	S	<b>Vinyl Driver</b>	0	0
6939510	S	<b>Non-Air Ride Passenger</b>	0	0
6939540	O	<b>Low Back Passenger</b>	0	0
6939570	S	<b>Vinyl Passenger</b>	0	0
7000055	O	<b>Flat Roof Overhead Storage</b>	195	0
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7001620	S	<b>Steering Wheel With Peterbilt Logo</b>	0	0

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Steering Wheel with embossed Peterbilt logo over horn button.		
7036140	S	<b>Probilt Interior Charcoal Gray - Flat Roof</b>	0	<b>0</b>
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	<b>0</b>
7210550	S	<b>1-Piece Glass Rear Cab Window Fixed</b>	0	<b>0</b>
7230060	S	<b>1-Piece Curved Windshield</b>	0	<b>0</b>
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0	<b>0</b>
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	<b>0</b>
7510060	O	<b>Aero Rear View Mirror Housing, Bright Finish</b>	162	<b>3</b>
7514010	O	<b>Peterbilt Aero Rear View Mirror, Motorized</b> Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	344	<b>3</b>
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0	<b>0</b>
7610500	S	<b>Air Horn Mounted Under Cab</b>	0	<b>0</b>
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	344	<b>11</b>
7725710	O	<b>Standard Speaker Package For Cab</b> (2) Speakers	55	<b>4</b>
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	41	<b>0</b>
7728050	O	<b>USB Port</b>	41	<b>0</b>
7788335	S	<b>Global Telematics Hardware</b>	0	<b>0</b>
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	<b>0</b>
7852020	O	<b>Cab Air Suspension</b>	212	<b>15</b>
7852050	O	<b>Auto Reset Circuit Protection</b> Daycab and Sleeper	19	<b>0</b>
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Fluorescent triangle emergency road flares are designed to meet and exceed all DOT standards.	33	<b>13</b>
7900310	O	<b>Fire Extinguisher, Mounted Outboard Driver Seat</b> Hazmat approval UL listed/rated ABC	66	<b>9</b>
7901130	O	<b>Backup Alarm (107 DB)</b>	34	<b>3</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
8011850	O	<b>Transmission Oil Temperature (Main)</b> Located in Digital Cluster Display.	29	<b>0</b>
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	<b>0</b>
8021630	O	<b>General Air Pressure 1 Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6.	182	<b>0</b>
8041200	O	<b>Dual Scale Speedometer MPH Over KPH</b>	0	<b>0</b>
8070860	S	<b>Main Instrumentation Panel</b> Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	<b>0</b>
8070940	O	<b>Voltmeter Gauge (MD/520 Only)</b> Located in Digital Cluster Display	0	<b>0</b>
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral DRL/Park, Turn, and Side Marker	0	<b>0</b>
8120980	S	<b>(5) Marker Lights, Aero LED</b> Standard Black Housing. Chrome Housing available with Sun Visor.	0	<b>0</b>
8134160	S	<b>Self-Canceling Turn Signal</b>	0	<b>0</b>
8134180	O	<b>Daytime Running Lights, Mounted In Bumper</b> Driven by chassis height	371	<b>0</b>
8140080	S	<b>LED Stop/Turn/Tail/Backup</b> Bracket mounted left-hand / right-hand end of frame	0	<b>0</b>
8140850	S	<b>Moveable EOF Crossmember For Mounting Tail Lights</b> Square end of frame with or without end of frame crossmember	0	<b>0</b>

### Paint

8500710	S	<b>Standard Paint Color Selection</b>	-200	<b>0</b>
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	<b>0</b>

### Shipping Destination

### Options Not Subject To Discount

9400091	S	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0	<b>0</b>
9400094	S	<b>PACCAR PX-9 Standard Coverage</b> 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	<b>0</b>
9408528	O	<b>Allison Surcharge 3000 Series Transmission</b>	700	<b>0</b>

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
9408634	O	<b>SmartLINQ RD - 5YR Sub</b> PACCAR PX Engines	799	<b>0</b>
9408701	O	<b>Base Warr: Emissions (CARB Operation)</b> 5YR/150K MI - PX-9 Engine	2,186	<b>0</b>
9408982	O	<b>Vehicle Layout</b> Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this.	1,500	<b>0</b>
<b>Miscellaneous</b>				
9409045	S	<b>Aero Hood (MODEL 548)</b>	0	<b>0</b>
9409072	O	<b>State Of Registry: Michigan</b>	0	<b>0</b>
9409645	O	<b>Model Year 2025 Engine</b>	0	<b>0</b>
9409749	O	<b>2024 Series Emissions Engine</b>	0	<b>0</b>

## Promotions

### Special Requirements

Special Requirement 1 0098170

Special Requirement 2

Special Requirement 3

Special Requirement 4

### Fuel Efficiency Score:

### Order Comments

**Total List Price (W/O Freight & Warranty & Surcharges )** \$177,685

**Marketing and Service Support Fee** \$1,595

**Prepaid Freight** \$3,625

**Total Surcharge/Options Not Subject To Discount** \$5,185

**Total Weight (lbs)** 16,491

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

### Prices and Specifications Subject to Change Without Notice.

Price Level: January 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC Tandem Pete Terex

Quote Number: QUO-1223362-K0T6G3

Printed On: 12/10/2025 10:32:53 AM



---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

#### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*





CSM - MICHIGAN KENWORTH - GRAND RAPIDS (M460)  
7393 EXPRESSWAY COURT SW  
GRAND RAPIDS, Michigan 49548

JACK DOHENY COMPANY  
777 DOHENY DR  
PO BOX 609  
NORTHVILLE, Michigan 48167  
United States of America

Jay Bowers  
Cell Phone: 9206001960  
Office Phone: 920-494-3696  
Email: jay.bowers@csmtruck.com

AMANDA HOLLEY  
Office Phone: 281-40202236  
Email: amandaholley@teamjdc.com

## Vehicle Summary

	<b>Unit</b>		<b>Chassis</b>
Model:	T480 Series Conventional	Fr Axle Load (lbs):	16000
Type:	FULL TRUCK	Rr Axle Load (lbs):	40000
Description 1:	JDC 6x4 Terex TL100	G.C.W. (lbs):	80000
Description 2:			
	<b>Application</b>		
Intended Serv.:	Local Pickup & Delivery: Vehicles which	Road Conditions: Class A (Highway)	90
Commodity:	Heavy Machinery	Class B (Hwy/Mtn) Class C (Off-Hwy) Class D (Off-Road)	10 0 0
	<b>Body</b>		
Type:	Flatbed	Maximum Grade:	6
Length (ft):	16	Wheelbase (in):	230
Height (ft):	13	Overhang (in):	130
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	69.5
	<b>Trailer</b>		
No. of Trailer Axles:		Cab to Axle (in):	160.5
Type:		Cab to EOF (in):	290.5
Length (ft):	0	Overall Comb. Length (in):	400
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
	<b>Restrictions</b>		<b>Special Req.</b>
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		U.S. Domestic Registry, 50-state.

Approved by:

Date:

**Note: All sales are F.O.B. designated plant of manufacture.**

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
<b>Model</b>			
0000480	S	<b>T480 Series Conventional</b>	<b>10,386</b>
0071000	O	<b>T480 Aero Hood</b>	<b>0</b>
0080050	O	<b>CARB Clean Idle Label - PACCAR PX Engines</b>	<b>0</b>
0080101	O	<b>CARB Low NOX Omnibus Registration Guidelines</b> Dealer/Customer acknowledges that this vehicle is NOT intended for registration or domicile/primary use in the State of California.	<b>0</b>
0080314	O	<b>EPA Clean Idle Label - PACCAR PX Engines</b>	<b>0</b>
0090162	O	<b>T480 Tandem</b>	<b>0</b>
0098422	O	<b>State of Registry: Michigan</b>	<b>0</b>
<b>Engine &amp; Equipment</b>			
0130221	O	<b>PACCAR PX-9 330 330@1750 1000@1200, 2024</b> With Turbo Exhaust Brake (VGT Brake) N09420 C333 0.....Reserve Speed Limit Offset ( N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 100...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 65....Max Vehicle Speed in Top Gea N09440 C234 NO....Engine Protection Shtdwn N09460 C231 NO....Gear Down Protection N09580 C133 5.....Idle Shtdwn Time N09680 C233 NO....Idle Shtdwn Override N09480 C132 1400..Max PTO Speed N09300 C128 65....Max Cruise Control Speed N09500 C239 NO....Cruise Control Auto Resume N09520 C238 NO....Auto Engine Brake in Cruise N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold N09560 C225 NO....Enable Idle Shutdown Park Br	<b>0</b>
1000047	O	<b>CARB Emissions Warranty Engine</b>	<b>0</b>
1000151	S	<b>PremierSpec</b>	<b>0</b>
1000243	O	<b>Gearing Analysis: Performance</b>	<b>0</b>

Price Level: August 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC 6x4 Terex TL100

Quote Number: QUO-1146237-R5G6Q7

Printed On: 12/10/2025 11:32:58 AM

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
		power before economy results.	
1000256	O	<b>Customer's Typical Operating Spd: 64 MPH</b>	<b>0</b>
1000344	O	<b>EWI Tracking - A2 Engine Module Chassis</b>	<b>0</b>
1000525		<b>Registration Year</b> Year of Registration: 2025	<b>0</b>
1000684		<b>Effective VSL Setting NA</b>	<b>0</b>
1000857	O	<b>Engine Idle Shutdown Timer Enabled</b>	<b>0</b>
1000891		<b>Eff EIST NA Expiration Miles</b> Use only with MX and Cummins engines	<b>0</b>
1002060	S	<b>Air Compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.</b>	<b>0</b>
1041399	S	<b>Air Cleaner: MD Composite Engine Mounted</b>	<b>0</b>
1098003	S	<b>Air Restriction Indicator: Mechanical</b> Mounted on Air Cleaner.	<b>0</b>
1105231	S	<b>Fan Hub: Horton On/Off for PX-9 or L9N</b>	<b>0</b>
1121231	S	<b>Cooling Module: 2.1M MD - Aero Hood</b> 1000 Square Inches	<b>0</b>
1160214	O	<b>Bug Screen: Behind Grille</b>	<b>2</b>
1247263	O	<b>EXH: Single Can 2024 RH Under with RH</b> Side-of-Cab Vertical Tailpipe	<b>0</b>
1290124	O	<b>Tailpipe: 5 in. single 24 in. 45 degree curved.</b>	<b>6</b>
1321102	S	<b>Fuel Filter: PACCAR 2.1M MD for PX-7 or PX-9</b> Fuel/water separator for 2021 and later engines.	<b>0</b>
1321205	O	<b>Run Aid: Fuel Heat</b> *For Fuel Filter	<b>0</b>
1321305	O	<b>Start Aid: 12V Heat</b> *For Fuel Filter	<b>1</b>
1504006	O	<b>Block Heater: PACCAR 750 watt 120V for PX-7 and B6.7N. 1000 watt for PX-9 and ISL9 Engines.</b>	<b>2</b>
1816260	S	<b>Alternator: PACCAR 160 amp, Brush Type</b>	<b>0</b>
1821220	S	<b>Batteries: 2 PACCAR GP31 Threaded Post (700-730)</b> 1400-1460 CCA dual purpose.	<b>0</b>
1836106	S	<b>Mitsubishi 105P55 12V Starter with Cummins and PX</b> PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. Only for Cummins or PX engines.	<b>0</b>
1840065	S	<b>12V Low Voltage Disconnect for Battery Protection</b>	<b>0</b>
1840067	O	<b>Battery Disconnect Switch Mounted on Battery Box</b>	<b>0</b>

Price Level: August 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC 6x4 Terex TL100

Quote Number: QUO-1146237-R5G6Q7

Printed On: 12/10/2025 11:32:58 AM

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
		Provides One (1) Switch	
1900996	O	<b>Jump Start Terminals Under Hood.</b>	<b>0</b>
1901018	S	<b>Remote PTO/Throttle, 12-Pin, 250K, Back of Cab</b> OR Back of Sleeper, J1939, Remote Control Provision	<b>0</b>
<b>Transmission &amp; Clutch</b>			
2011631	O	<b>Transmission: Allison 3500RDS 6-speed, With PTO</b> drive gear. Limited to 1050LBFT. 6th Generation Controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	<b>443</b>
2401405	O	<b>Driveline: 2 Dana Standard-Duty; 1 Centerbearing.</b> *Standard duty is 1710 series.	<b>-1</b>
2406005	O	<b>45 degree Yokes on Interaxle Drivelines.</b>	<b>0</b>
2409941	S	<b>One Heavy-Duty One-Piece Aluminum Crossmember</b> This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	<b>0</b>
2410018	O	<b>Torque Converter Included W/ Allison</b> Transmission.	<b>0</b>
2410153	O	<b>Push Button Shifter Controls, Center Console</b> Mounted for Allison Transmission. 2.1m Medium Duty only.	<b>0</b>
2410204	O	<b>Allison Fuel Sense: Delete</b>	<b>0</b>
2410244	O	<b>J1939 Park Brake Auto Neutral</b>	<b>0</b>
2410310	O	<b>Allison Neutral at Stop</b>	<b>0</b>
2410426	U	<b>Allison RDS Package 223</b> Narr Allison RDS Package 223	<b>0</b>
2429378	O	<b>Customer Installed Transmission PTO in the LH</b> Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	<b>0</b>
<b>Front Axle &amp; Equipment</b>			
2517016	O	<b>Meritor MFS20 Front Axle 16K 3-1/2in drop</b> standard track.	<b>139</b>
2641137	O	<b>Front Brakes: 20K Meritor Q-Plus 16.5x6 in.</b>	<b>-38</b>
2690035	O	<b>Front Brake Drum: 22K 16.5x6 in. cast.</b>	<b>104</b>
2702020	O	<b>Front Hubs Iron Hub Pilot 20,000 lbs. 10 Bolt</b> 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle. Consider Wheelguards (5850002) with aluminum wheels.	<b>80</b>
2741970	S	<b>ConMet PreSet Plus Hub Package; Front Axle.</b>	<b>0</b>
2750001	S	<b>Hubcap: Front Vented.</b>	<b>0</b>

Price Level: August 1, 2025

Deal: JDC 6x4 Terex TL100

Printed On: 12/10/2025 11:32:58 AM

100% Complete

Date: December 10, 2025

Quote Number: QUO-1146237-R5G6Q7



Sales Code	Std/ Opt	Description	Weight
2765001	S	<b>Front Auto Slack Adjuster for Drum Brakes.</b>	0
2864074	O	<b>Front Springs: Taperleaf 16K W/ Shock Absorbers</b> w/ maintenance-free elastomer spring pin bushings.	99
2895300	O	<b>Dual Power Steering Gears: 16K.</b>	75
2899336	O	<b>Power Steering Cooler:Radiator Mounted Air-to-Oil</b>	11
2900055	O	<b>5 mm Front Suspension Spacer Block</b>	0
2900612	O	<b>Threaded Front Spring Bushings in Place of</b> elastomeric.	0
<b>Rear Axle &amp; Equipment</b>			
3122247	O	<b>Dual Meritor MT40-14x4 Hypoid Rear Axle</b> rated at 40K, with heavy-wall housing. Tandem rear axles.	2,001
3200586	O	<b>Rear Axle Ratio - 5.86.</b>	0
3354004	O	<b>Dual Rear Brakes 16-1/2x7 in. to 46K;</b> Meritor Q-Plus S-cam stamped spider.	16
3392005	O	<b>Dual Rear Brake Drums: Cast.</b> For use with 16.5X7" or 16.5X8.625" brake.	0
3407050	O	<b>Dual Rear Hubs: Aluminum Hub Pilot 46K;</b> 11.25" bolt circle. Requires "R" series outer ends.	0
3441972	O	<b>ConMet PreSet Plus Hub Package; Dual Rear Axle.</b>	0
3465002	O	<b>Tandem Rear Axle Automatic Slack Adjusters.</b> For use with drum brakes.	0
3485207	O	<b>Spring Brake: 3030 Long Stroke Dual 30 Square</b> inches travel. For drum brakes. Helps keep brakes in adjustment longer.	4
3495226	S	<b>Bendix 4S/4M Anti-Lock Brake System.</b>	0
3500037	O	<b>Interaxle Driveline:1 Dana 1710 Series</b> Tandem Rear Axles Only.	86
3737455	O	<b>Rear suspension: Tandem Hendrickson RT403 40K.</b> 52 in. axle spacing. 7.19 in. saddle height w/barpin bushing. Unladen Height: 10.7 in. Laden Height: 9.7 in. Advertised axle spacing for this rear suspension is a nominal value. Actual spacing may be up to two inches greater than noted. This is important in situations where the body is likely to be pre-built before the chassis is delivered. Tire to body or bracket to body interference may be encountered. Communicate clear space requirements on the sales order. DSP40/P rear axles are not for use with Hendrickson HAS 402, Hendrickson Primaax, or Hendrickson beam-type rear suspensions. Hendrickson RT403 rear suspension for use with tandem axles up to 46K on T8 series. Hendrickson RT403 rear suspension requires bronze center bushings when used in refuse loader or packer applications.	461



Sales Code	Std/ Opt	Description	Weight
3832315	O	<b>Bolted Rear Suspension Crossmembers for RT403 or HAS402.</b> Replaces medium duty standard.	0
<b>Tires &amp; Wheels</b>			
4077406	O	<b>Front tires: Bridgestone M864 385/65R22.5 18PR</b> All position. On/Off highway. Wide-base tire.	114
4277487	O	<b>Rear tires: Bridgestone M799 11R22.5 16PR.</b> 42 in. diameter, drive. 19.5 in. SLR. Code is priced per pair of tires.	80
4900008	O	<b>Rear Tire Quantity: 8</b>	0
5042299	O	<b>Front Wheel: Accuride 29374 22.5x12.25 aluminum,</b> Standard polish finish, hub-pilot mount. 11000lb. maximum rating. 5.80 in. offset. Air disc brake compatible.	-2
5242338	O	<b>Rear Wheel: Accuride 43644 22.5X8.25 aluminum hub</b> pilot mount standard polish	-208
5900008	O	<b>Rear Wheel/Rim Quantity: 8</b>	0
<b>Frame &amp; Equipment</b>			
6056600	O	<b>Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 337in.</b> to 416 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	568
6141600	O	<b>Full Steel Insert: for 10-5/8 in. or 10-3/4 in.</b> Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model. See databook addendum section 7.2.	793
6308715	O	<b>Bumper: Aerodynamic Chrome Steel. Requires a</b> bumper setting code.	68
6319040	S	<b>40 in. Bumper Setting. Requires a Bumper Code.</b>	0
6321010	S	<b>Front Tow Loops: Two</b>	0
6391299	U	<b>Custom Frame 50+</b> CFL C/M: TBD	0
6400644	O	<b>Battery Box Cantilever Aluminum BOC with Smooth</b> natural finish aluminum cover.	19
6409901	S	<b>Battery Box Location: LH Side.</b>	0
6451125	S	<b>DPF/SCR Box Natural End Plates and Natural</b> cover.	0
6490139	S	<b>Heavy-Duty One-PC Aluminum Intermediate/ Fill-In</b> crossmember.	0

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
6490433	S	<b>Heavy-Duty 5-Piece Rear Cab Support, Hucked assembly.</b> Huck fastened to frame.	0
6721102	S	<b>Rear Mudflap Arms: Betts B-25 Standard-Duty,</b> straight. Includes B1732 mounting brackets as standard.	0
6722000	S	<b>Rear Mudflap Shields: White Plastic Antisail W/ Kenworth logo.</b>	0
6742009	S	<b>Square End-of-Frame W/O Crossmember; Non-Towing.</b>	0
<b>Fuel Tanks &amp; Equip</b>			
7140050	O	<b>50 US Gallon D-Shape Rectangular Aluminum Under fuel tank, replace.</b> With non-slip step.	22
7722170	S	<b>Small DEF Tank, 5.5 Gallons.</b>	0
7889203	O	<b>DEF to Fuel Fill Ratio 2:1 or Greater.</b>	0
7889606	O	<b>DEF Tank Location is LH Under Cab.</b>	0
7920050	O	<b>Location: 50 gal fuel tank LH under cab.</b>	0
<b>Cab &amp; Equipment</b>			
8024311	S	<b>Cab: Stamped Aluminum with Curved Windshield</b> LED markers. Requires separate roof code.	0
8090155	O	<b>Hood: Med Aero w/ Chrome Crown</b>	0
8108011	S	<b>Cab HVAC - Day Cab and 40 in. Sleeper</b> System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0
8201013	S	<b>Steering Wheel: 18 in. 4-Spoke.</b>	0
8201200	S	<b>Adjustable Telescoping Tilt Steering Column.</b>	0
8205135	O	<b>Information for Customer-Installed PTO Muncie 10-bolt.</b>	0
8205177	O	<b>Dash Switch:1st Allison-Mounted PTO.</b> Electric switch and wiring are factory-installed to control the 1st Allison Trans mounted PTO.	0
8208497	O	<b>Four Spare Switches: Wired to Power.</b>	0
8222411	O	<b>Gauge: DD Virtual Gauge - Eng Pto Hour</b>	0
8282024	S	<b>Main Instrument Package: 7" Digital Display</b> Cluster. Includes Physical (Analog): Speedometer, Tachometer, Oil Pressure, and Coolant Temp; and Digital: Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air	0

Price Level: August 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC 6x4 Terex TL100

Quote Number: QUO-1146237-R5G6Q7

Printed On: 12/10/2025 11:32:58 AM

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
		Pressure, Secondary Air Pressure, and Air Application for air brake trucks.	
8330591	S	<b>Interior Trim Package: 2.1M MD Gray Foam</b> Backing/Cloth Headliner W/Gray Sunvisor & Seat Color Three Underdash Center Console Cupholders (Two If Allison Transmission Is Selected).	0
8410107	O	<b>Driver Seat : KW Air Seat HB Tough Cloth</b> w/o Armrests w/ Susp Cover	0
8478056	O	<b>Rider Seat: KW Toolbox 2-Man Bench Tough Cloth</b>	0
8601432	O	<b>Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth</b>	0
8698965	O	<b>Speaker Package For Cab: (2) Speakers</b> B-Pillar	0
8700196	S	<b>Turn Signal: Self-Cancelling</b>	0
8700283	S	<b>LH and RH Trip Ledge Rain Deflectors</b>	0
8700601	S	<b>Global Telematics Unit</b>	0
8800402	S	<b>Dual Cab Interior Grabhandles: A Pillar Mounted</b> Dash Wrap and B Pillar Mounted Grabhandles	0
8832113	S	<b>Kenworth Daylite Door With Standard LH/RH</b> electric door locks and LH/RH electric window controls.	0
8841411	S	<b>Single Air Horn Under Cab.</b>	0
8850139	S	<b>Look-Down, Pass. Door, Black 11x6</b>	0
8850842	S	<b>Mirror Shell: Dual Aero In-Mold Black</b>	0
8860853	S	<b>Mirror: Dual KW Aero Rear View</b> Non-Motor, Non-Heated with Integral CX	0
8871446	S	<b>Rear Cab Stationary Window 19in x 36in</b>	0
8890101	S	<b>One-Piece Bonded-In Windshield With Curved Glass.</b> Standard.	0
8890356	O	<b>4 1/4" Molded Wheelwell Fender Extension.</b>	0
8890874	O	<b>Kenworth Cab Air Suspension.</b>	0
8891011	O	<b>Roof: Raised Profile, Stamped Aluminum w/</b> Additional Head Room & Interior Overhead Storage	0
<b>Lights &amp; Instruments</b>			
9010803	S	<b>Headlamps: Single Halogen Complex Reflector w/</b> Turn Indicator, Reflector and DRL. Fender Mtd.	0
9022137	S	<b>Marker Lights: Five Rectangular LED.</b>	0

Price Level: August 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC 6x4 Terex TL100

Quote Number: QUO-1146237-R5G6Q7

Printed On: 12/10/2025 11:32:58 AM

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
9030052	S	<b>LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.</b>	0
9080206	O	<b>Switch &amp; Wiring: Customer-Installed Beacon Lights</b> with additional 20 ft jumper harness shipped loose.	1
9090115	O	<b>Reflectors: Two Midframe</b>	0
<b>Air Equipment</b>			
9101218	S	<b>Air Dryer: Bendix AD-HF Puraguard Heated</b>	0
9108001	S	<b>Moisture Ejection Valve W/ Pull Cable Drain.</b>	0
9110020	O	<b>Full Truck Kit</b> Gladhands mounted at end-of-frame. Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard.	15
9140020	S	<b>Nylon Air Tubing in Frame &amp; Cab, Excluding Hoses</b> subject to excessive heat or flexing.	0
9140200	O	<b>Delete Trailer Hand Valve--Req Full Truck or Trac Kit</b>	0
9140328	O	<b>Trailer ABS Electric Supply Through SAE J560</b> 7-pin connector per TMC RP137).	0
<b>Extended Warranty</b>			
9200008	S	<b>Base Warranty - PACCAR PX-9 Engine</b> 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
9200113	O	<b>Severe Service Medium-Duty Warranty: 12 months/</b> 50,000 miles & km	0
9210402	O	<b>Allison 3000 Series Transmission Surcharge</b>	0
9212661	O	<b>TruckTech+ RD - 5YR Sub PACCAR PX Engines</b>	0
9220016	O	<b>Base Warranty: Emissions (CARB Operation) PX-9</b> 5YR/150K MI	0
<b>Miscellaneous</b>			
9409852	O	<b>GHG Secondary Manufacturer: Does Not Apply</b>	0
9491652	S	<b>EMUX Architecture</b>	0
<b>Promotions</b>			
<b>Paint</b>			
9700000	O	<b>Paint Color Number(s).</b>	0

Price Level: August 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC 6x4 Terex TL100

Quote Number: QUO-1146237-R5G6Q7

Printed On: 12/10/2025 11:32:58 AM

**KENWORTH**

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
		N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK	
9943004	S	<b>Bumper Unpainted</b>	0
9943048	O	<b>Day Cab Bulk Paint</b>	0
9943050	S	<b>Day Cab Standard Paint</b>	0
9944820	S	<b>1 - Color Paint - Day Cab</b> Color will be White if no other color is specified.	0
9965510	S	<b>Base Coat/ Clear Coat.</b> The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

**Special Requirements**

Special Requirement 1 0098025

Special Requirement 2

Special Requirement 3

Special Requirement 4

**Fuel Efficiency Score:****Order Comments****Total Weight (lbs)** 15,347

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

**Prices and Specifications Subject to Change Without Notice.**

---

Unpublished options may require review/approval.

---

Dimensional and performance data for unpublished options may vary from that displayed in CRM.**PRICING DISCLAIMER**

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors

Price Level: August 1, 2025

100% Complete

Date: December 10, 2025

Deal: JDC 6x4 Terex TL100

Quote Number: QUO-1146237-R5G6Q7

Printed On: 12/10/2025 11:32:58 AM



*or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*

---

Price Level: August 1, 2025  
Deal: JDC 6x4 Terex TL100  
Printed On: 12/10/2025 11:32:58 AM

100% Complete

Date: December 10, 2025  
Quote Number: QUO-1146237-R5G6Q7



# KENWORTH

## Shipping Destinations

Intermediate Destination:

Final Destinations	Quantity

Price Level: August 1, 2025

Deal: JDC 6x4 Terex TL100

Printed On: 12/10/2025 11:32:58 AM

100% Complete

Date: December 10, 2025

Quote Number: QUO-1146237-R5G6Q7